

## TYRE LINE-UP

Duravis R-Steer 002



### GENERAL INFO

| Tyre size     | Load    | Speed | Section Width (mm) | Diameter Overall (mm) | Static Loaded Radius (mm) | Rolling Circ.(mm) @ 90 km/h (Tol,±2%) | Rim (Inch) Measuring | Rim (inch) Optional | Fuel Efficiency | Wet Grip | Rolling noise level | Rolling noise dB | Mud & Snow | Mountain & Snow Flake | RFID |
|---------------|---------|-------|--------------------|-----------------------|---------------------------|---------------------------------------|----------------------|---------------------|-----------------|----------|---------------------|------------------|------------|-----------------------|------|
| 295/80 R 22.5 | 154/149 | M     | 305                | 1051.2                | 490                       | 3195                                  | 9.00                 | 8.25                | B               | B        | A                   | 70               | V          | V                     | V    |
| 315/80 R 22.5 | 156/150 | L     | 314                | 1077                  | 500                       | 3272                                  | 9.00                 | 9.75                | B               | A        | A                   | 71               | V          | V                     | V    |
| 315/80 R 22.5 | 154/150 | M     | 314                | 1077                  | 500                       | 3272                                  | 9.00                 | 9.75                | B               | A        | A                   | 71               | V          | V                     | V    |
| 315/70 R 22.5 | 156/150 | L     | 313                | 1017                  | 469                       | 3091                                  | 9.00                 | 9.75                | B               | B        | A                   | 71               | V          | V                     | V    |
| 315/70 R 22.5 | 154/150 | M     | 313                | 1017                  | 469                       | 3091                                  | 9.00                 | 9.75                | B               | B        | A                   | 71               | V          | V                     | V    |
| 385/65 R 22.5 | 160     | K     | 376                | 1075.6                | 497                       | 3269                                  | 11.75                | 12.25               | B               | B        | A                   | 69               | V          | V                     | V    |
| 385/65 R 22.5 | 158     | L     | 376                | 1075.6                | 497                       | 3269                                  | 11.75                | 12.25               | B               | B        | A                   | 69               | V          | V                     | V    |
| 315/60 R 22.5 | 154/148 | L     | 322                | 957.2                 | 448                       | 2910                                  | 9.75                 | 9.00                | C               | B        | A                   | 70               | V          | V                     | V    |
| 385/55R 22.5  | 160     | K     | 381                | 1001                  | 466                       | 3041                                  | 12.25                | 11.75               | B               | B        | B                   | 72               | V          | V                     | V    |
| 385/55R 22.5  | 158     | L     | 381                | 1001                  | 466                       | 3041                                  | 12.25                | 11.75               | B               | B        | B                   | 72               | V          | V                     | V    |

